

## REFRIGERATED PIZZA COUNTER THREE COMPARTMENTS WITHOUT WORKTOP

Refrigerated table for pizza, made with internal and external monocoque structure in AISI 304 stainless steel. Cooling system with finned evaporator and electric fan, automatic defrosting and automatic condensation drain. Electronic thermometer-thermostat. Unit without working top. 3 refrigerated compartments, doors with stainless steel handle.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption, kWh/24h	3,64
Energy consumption/year, kWh/a	1327	Energy Efficiency Class	C
Energy Efficiency Index	48,99	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	50	Net usable volume, lt	360
Refrigerant charge, kg	0,08	Refrigerant/GWP	R290/3
Refrigeration power at -10°C W	560	Temperature ranges, °C	+2/+10
Volume, gross, lt	564		

### Functional features

- Model with 3 refrigerated doors-compartments.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Noise level <70 dBA.
- The appliance's outstanding reliability is also assured by the IP24 protection of its functional elements.
- For compartment: ventilated refrigeration system obtained through a painted finned evaporator, with protection and electric fan. Air circulation "U" system in the engine compartment with front air intake in the room and frontal expulsion of the hot air. The high humidity value, in the measure of 90%, guarantees an ideal preservation of "pizza balls".

### Constructional features

- Model without worktop.
- One-piece structure in AISI 304 stainless steel with rounded internal corners, insulation system in polyurethane foam without the use of CFCs. Door, sides and dashboard in satin finish. Scotchbrite finish. Glossy internal finish. Variable insulation thickness: from 60 to 40 mm.
- The cooling unit pulls out to simplify routine cleaning of the condenser. "U"-flow air circulation to assure peak cooling unit reliability.
- Compartment refrigerant fluid: R290.
- Door with self-closing system for openings of less than 90 °. Stainless steel handle integrated, easy to grip. Easily removable magnetic gasket. Depth with open door: 118 cm.
- Refrigerated compartment useful for Euronorm containers 60x40 cm; racks in AISI 304 stainless steel to support grids / containers, which can be easily removed.
- Drain hole at the bottom to facilitate cleaning operations.
- Evaporator with an anti-corrosion treatment.
- Stainless steel height-adjustable feet.

### Standard equipment

- Each compartment / door supplied with: 1 pair of stainless steel runners for supporting grids / basins.

# BZ25



## Optionals and Accessories

- For refrigerated compartment: runners for 60x40 cm containers, 60x40 cm containers, wheels.

## Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	140 kg
<i>Gross Weight</i>	160 kg	<i>Electric Power</i>	0,32 kW
<i>Dimensions</i>	206x72,5x83 cm	<i>Packing</i>	211x81x104 cm

REFRIGERATED PIZZA COUNTER THREE COMPARTMENTS WITHOUT WORKTOP