

REFRIGERATED DISPLAY UNIT +14 ÷ +16°C COLOR BLACK

Vertical refrigerated display unit. Display compartment double-glazed with tempered glass, outside screen-printed. Color: black. Lighting through high brightness LED bars. Nr. 5 tempered glass shelves, rear support racks in AISI 304 stainless steel. Ventilated refrigeration with evaporator positioned in the lower part of the structure. Control panel with electronic PCB, capacitive keys, HACCP alarms. Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0).



<i>Climate class</i>	4 (+30°C, 55% R.H.)	<i>Energy Efficiency Class</i>	product excluded from the European energy classification label according to EU Regulation 2019/2018
<i>Refrigeration power at -10°C W</i>	362	<i>Temperature ranges, °C</i>	+14/+16
<i>Volume, gross, lt</i>	324		

Functional features

- Operating temperature: +14°C ÷ +16°C.
- Relative humidity: 40/44%. Relative humidity control with humidistat, specialising these models for the artisan chocolate sector.
- Power unit with refrigerant fluid R290.
- The control panel, with electronic circuit board with capacitive keys and communication port, is concealed by the bottom structure, although the display is always in view for monitoring correct operation of the unit. It allows precise control of operating parameters as well as HACCP alarm alerts.
- Snap removable front dashboard for compressor cleaning operations.
- Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0).

Constructional features

- Display compartment double-glazed throughout with black screen-printed tempered glass. Bottom structure in black (RAL 9005).
- Display cabinet with 5 tempered glass shelves. Dimensions of each shelf: 49 x 47 cm. Max load per shelf 12 kg. Rear support on racks in AISI 304 stainless steel.
- Door with integrated full-height handle, easy to take, not reversible on site. Easily removable magnetic gasket.
- Ventilated refrigeration through finned evaporator with anti-corrosion treatment, positioned in the lower part of the structure.
- Dynamic lighting with anti-glare high-luminosity LED strips: the type of light can be varied depending on the product displayed (3000K – 4000K – 5000K – 6000K). The display unit is also fitted with PIR Sense proximity sensor, which changes the light intensity as customers approach.
- Wheels and feet integrated in the lower structure (4).
- Installation allowed to an altitude up to 800 metres above sea level.

Standard equipment

- 5 tempered glass shelves.

Optional

- Accessory for display of bottles (diameter: 75 mm) vertical, horizontal or a combination of the two. Maximum vertical bottle capacity 42 on three shelves.
- Tempered glass shelf
- Plnith.
- APOLINK accessory: connectivity to APO.LINK portal for remote control of appliance (Industry 4.0).

Technical Data



C6A



Working voltage 230V 1N~ / 50Hz

Net Weight 178 kg

Gross Weight 198 kg

Electric Power 0,33 kW

Dimensions 60x64,5x184 cm

Packing 74x76x202 cm

REFRIGERATED DISPLAY UNIT +14 ÷ +16°C COLOR BLACK
Vetrine refrigerate New Style