

REFRIGERATED DISPLAY UNIT +14 ÷ +16°C
COLOR GREY

Vertical refrigerated display cabinet. Display cabinet made in in hardened double glazing, silk-screened exterior, lower structure in special steel on wheels. Color: grey. Lighting through LED lights. Nr. 5 tempered glass shelves, rear support racks in AISI 304 stainless steel. Control panel with electronic PCB, capacitive keys, HACCP alarms. Ventilated refrigeration with evaporator positioned in the lower part of the structure.



Climate class	4 (+30°C, 55% R.H.)	Refrigeration power at -10°C W	442
Temperature ranges, °C	+14/+16	Volume, gross, lt	457

Functional features

- Operating temperature: +14°C ÷ +16°C.
- Relative humidity: 40/44%. Relative humidity control with humidistat, specialising these models for the artisan chocolate sector.
- Power unit with refrigerant fluid R290.
- Electronic control board with HACCP alarm signalling.
- Snap removable front dashboard for compressor cleaning operations.

Constructional features

- Display cabinet made entirely of hardened double glazing, with grey silk-screened glass. Lower structure in grey special steel.
- Display cabinet with 5 tempered glass shelves. Dimensions of each shelf: 70 x 47 cm. Max load per shelf 12 kg. Rear support on racks in AISI 304 stainless steel.
- Door with integrated full-height handle, easy to take, not reversible on site. Easily removable magnetic gasket.
- Ventilated refrigeration through finned evaporator with anti-corrosion treatment, positioned in the lower part of the structure.
- Interior lighting in refrigerated display through LED bars, front on the back of the door.
- Wheels and feet integrated in the lower structure (4).
- Installation allowed to an altitude up to 800 metres above sea level.

Standard equipment

- 5 tempered glass shelves.

Optional

- Accessorio per l'esposizione di bottiglie (diametro: 75mm) in verticale, orizzontale oppure mista. Massimo numero di bottiglie in verticale n. 84 su tre ripiani.

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	211 kg
Gross Weight	236 kg	Electric Power	0,3 kW
Dimensions	80,5x64,5x184 cm	Packing	89x76x202 cm