

TABLE WITH REAR SPLASHBACK 200 CM

AISI 304 stainless steel top, thickness 0.8 mm, 40 mm h, rear splashback 100 mm h. Sound deadening, water-fireproof chipboard panel underneath, thickness 18 mm. Legs made of tubular stainless steel 40x40 mm with under shelf. AISI 304 stainless steel 1" feet, height adjustable 60 mm. Assembly with screw, working table is delivered disassembled.



<i>Rear splashback</i>	yes	<i>Working side</i>	One working side
------------------------	-----	---------------------	------------------

Functional features

- Worktop version with rear splashback height 100 mm, integral with the worktop itself, base radiused.
- Ergonomics, offering a standard height of 90 cm from the floor.
- Height adjustable feet for ground leveling.

Constructional features

- Worktop h = 40 mm made in AISI 304 stainless steel sheet, thickness 8-10 of mm with upturned edges and soundproofing. Under panel made in melamine faced chipboard, water and sound proof, thickness 18 mm.
- Nr. 4 legs made of stainless steel tubular 40x40 mm, thickness 10/10 of mm, pre-set for mounting the bottom shelf. 1" feet made of AISI 304 stainless steel, adjustable in height of 60 mm, threaded inserts in gray nylon.
- Working table is delivered disassembled. Assembly through interlocking system with screws.

Safety equipment and approvals

- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

Standard equipment

- Bottom shelf (supplied disassembled).

Optional

- Drawer, drawers units, wheels.

Technical Data

<i>Net Weight</i>	73,2 kg	<i>Gross Weight</i>	75 kg
<i>Dimensions</i>	200x70x90 cm	<i>Packing</i>	200x70x25 cm

700 line EcoLine
TABLE WITH REAR SPLASHBACK 200 CM