EA16A1



CUPBOARD WITH SLIDING DOORS, REAR SPLASHBACK

AISI 304 stainless steel top, thickness 0.8 mm, 40 mm h, rear splashback 100 mm h. Sound deadening, water-fireproof chipboard panel underneath. Standing-structure closed by stainless steel panels. Internal shelf in stainless steel thickness 0.8 mm, 3 height adjustable. Stainless steel sliding soundproofing double-skin doors. AISI 304 tubular stainless steel feet (diameter 50 mm), height adjustable 60 mm.





Working side

One working side

Functional features

- · Worktop version with rear splashback height 100 mm, integral with the worktop itself, base radiused.
- · Ergonomics, offering a standard height of 90 cm from the floor.
- · Height adjustable feet for ground leveling.

Constructional features

- · Worktop h = 40 mm made in AISI 304 stainless steel sheet, thickness 8-10 of mm with upturned edges and soundproofing. Under panel made in melamine faced chipboard, water and sound proof, thickness 18 mm.
- · Standing-structure closed by stainless steel panels. Internal shelf in AISI 430 stainless steel thickness 0.8 mm, 3 height adjustable.
- · Sliding soundproofed double-skin doors made of AISI 430 stainless steel.
- · Handle obtained from the door, with handsafe fold.

Safety equipment and approvals

 The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

Optional

· Wheels.

Technical Data

Net Weight	74,1 kg	Gross Weight	78 kg
Dimensions	160x70x90 cm	Packing	160x70x100 cm



700 line Ecoline