

## CUPBOARD WITH SLIDING DOORS AND DRAWERS, REAR SPLASHBACK

AISI 304 stainless steel top, thickness 0.8 mm, 40 mm h, rear splashback 100 mm h. Sound deadening, water-fireproof chipboard panel underneath. Standing-structure closed by stainless steel panels. Internal shelf in stainless steel thickness 0.8 mm, 3 height adjustable. Stainless steel sliding soundproofing double-skin doors. 3 drawers GN 1/1 with front panel in stainless steel. AISI 304 tubular stainless steel feet (diameter 50 mm), height adjustable 60 mm.



Working side

One working side

### Functional features

- Worktop version with rear splashback height 100 mm, integral with the worktop itself, base radiused.
- Ergonomics, offering a standard height of 90 cm from the floor.
- Height adjustable feet for ground leveling.

### Constructional features

- Worktop h = 40 mm made in AISI 304 stainless steel sheet, thickness 8-10 of mm with upturned edges and soundproofing. Under panel made in melamine faced chipboard, water and sound proof, thickness 18 mm.
- Standing-structure closed by stainless steel panels. Internal shelf in AISI 430 stainless steel thickness 0.8 mm, 3 height adjustable.
- Sliding soundproofed double-skin doors made of AISI 430 stainless steel.
- Handle obtained from the door, with handsafe fold.
- Drawer unit with 3 drawers GN 1/1 with front panel in AISI 430 stainless steel.

### Safety equipment and approvals

- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

### Optional

- Wheels.

### Technical Data

Net Weight	90 kg	Gross Weight	100 kg
Dimensions	180x70x90 cm	Packing	190x80x100 cm

CUPBOARD WITH SLIDING DOORS AND DRAWERS, REAR SPLASHBACK  
700 line EcoLine