

CUPBOARD WITH HINGED DOOR, DOUBLE SIDE TOP

AISI 304 stainless steel double side top, thickness 0.8 mm, 40 mm h. Sound deadening, water-fireproof chipboard panel underneath. Standing-structure closed by stainless steel panels. Internal shelf in stainless steel thickness 0.8 mm, 3 height adjustable. Stainless steel hinged double-skin soundproofing doors. AISI 304 tubular stainless steel feet (diameter 50 mm), height adjustable 60 mm.



Rear splashback

no

Functional features

- Double sided worktop version.
- Ergonomics, offering a standard height of 90 cm from the floor.
- Height adjustable feet for ground leveling.

Constructional features

- Worktop h = 40 mm made in AISI 304 stainless steel sheet, thickness 8-10 of mm with upturned edges and soundproofing. Under panel made in melamine faced chipboard, water and sound proof, thickness 18 mm.
- Standing-structure closed by stainless steel panels. Internal shelf in AISI 430 stainless steel thickness 0.8 mm, 3 height adjustable.
- Hinged soundproofed double-skin doors made of AISI 430 stainless steel.
- Handle obtained from the door, with handsafe fold.

Safety equipment and approvals

- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

Optional

- Wheels.

Technical Data

Net Weight

40 kg

Gross Weight

50 kg

Dimensions

80x70x90 cm

Packing

90x80x100 cm

CUPBOARD WITH HINGED DOOR, DOUBLE SIDE TOP

700 line EcoLine