

## CUPBOARD WITH HINGED DOOR, REAR SPLASHBACK

AISI 304 stainless steel top, thickness 0.8 mm, 40 mm h, rear splashback 100 mm h. Sound deadening, water-fireproof chipboard panel underneath. Standing-structure closed by stainless steel panels. Internal shelf in stainless steel thickness 0.8 mm, 3 height adjustable. Stainless steel hinged double-skin soundproofing doors. AISI 304 tubular stainless steel feet (diameter 50 mm), height adjustable 60 mm.



Rear splashback                      yes

### Functional features

- Worktop version with rear splashback height 100 mm, integral with the worktop itself, base radiused.
- Ergonomics, offering a standard height of 90 cm from the floor.
- Height adjustable feet for ground leveling.

### Constructional features

- Worktop h = 40 mm made in AISI 304 stainless steel sheet, thickness 8-10 of mm with upturned edges and soundproofing. Under panel made in melamine faced chipboard, water and sound proof, thickness 18 mm.
- Standing-structure closed by stainless steel panels. Internal shelf in AISI 430 stainless steel thickness 0.8 mm, 3 height adjustable.
- Hinged soundproofed double-skin doors made of AISI 430 stainless steel.
- Handle obtained from the door, with handsafe fold.

### Safety equipment and approvals

- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

### Optional

- Wheels.

### Technical Data

|                   |              |                |               |
|-------------------|--------------|----------------|---------------|
| <i>Dimensions</i> | 100x70x90 cm | <i>Packing</i> | 110x80x100 cm |
|-------------------|--------------|----------------|---------------|

CUPBOARD WITH HINGED DOOR, REAR SPLASHBACK  
700 line EcoLine