

FREEZER -20°C ÷ -10°C GN 2/1 ANTI-FINGERPRINT STEEL

Refrigerator with internal and external one-piece structure special anti-fingerprint steel. Storage chamber equipped with shelf supports in AISI 304 stainless steel, 21 levels. Ventilated cooling system, evaporator positioned outside the refrigerating chamber. Control panel with digital thermometer-thermostat. Electric defrosting. Delivered as standard with: 6 plastified GN 2/1 grids, 6 pairs of AISI 304 stainless steel guides and 3 plastified connecting grids.



Capacity	I 1500	Climate class	5 (+40°C, 40% R.H.)
Energy consumption, kWh/24h	17,6	Energy consumption/year, kWh/a	6424
Energy Efficiency Class	F	Energy Efficiency Index	94,55
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C	LWA dB(A)	67
Net usable volume, lt	1080	Refrigerant charge, kg	0,14
Refrigerant/GWP	R290/3	Refrigeration power -23,3°C W	750
Temperature range	-20/-10°C	Volume, gross, lt	1180

Functional features

- Operating temperature: -20°C ÷ -10°C.
- Reliability tested up to + 43°C.
- Power unit with refrigerant fluid R290.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- Automatic condensation evaporation.
- Easy access to all controls and parts from the control board.
- Microswitch for internal fan stop and lamp switch on when door is open.

Constructional features

- One-piece construction structure made of special anti-fingerprint steel, inner rounded corners, CFC-free polyurethane insulation.
- Insulation thickness: 75 mm.
- Ventilated refrigeration system through finned evaporator with anti-corrosion treatment, positioned outside the refrigerating chamber means more storage space available.
- Racks made of AISI 304 stainless steel, easily removable, 21 positions rack, 60 mm clearance.
- Doors on AISI 304 stainless steel hinges, equipped with a self-closing device for openings inferior to 90°. Integrated full-height handle with easy grip. Magnetic gasket, easily removable.
- Depth with door open: 1475 mm.
- Lighting through LED lamp with easy access.
- Key-operated lock.
- Stainless steel AISI 304 stainless steel h 150 mm, adjustable in height from 115 to 165 mm.

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	199 kg
-----------------	-----------------	------------	--------

EF15B



Gross Weight	219 kg	Electric Power	0,92 kW
Dimensions	150x80x204 cm	Packing	154x85,5x207 cm

Refrigerators
FREEZER -20°C ÷ -10°C GN 2/1 ANTI-FINGERPRINT STEEL