

## WALL MOUNTED HAND WASH BASIN, KNEE LEVEL OPERATED

Top with 40 mm height in AISI 304 stainless steel, 0.8 mm thick. Rear splashback h = 100 mm. Pressed well made of 0.8 mm thick AISI 304 stainless steel, diameter 340, height 135 mm. Closed supporting structure with stainless steel panels, 0.8 mm thick. Equipped with timed water supply button and tap, drain and drain trap, hot/cold water mixing valve.



### Functional features

- Moulded well made of 0.8 mm thick AISI 304 stainless steel, diameter 340, height 135 mm. Rounded corners.
- Equipped with timed water supply button and tap.
- Knee-operated water supply control.

### Constructional features

- Supporting structure closed by stainless steel panels, 0.8 mm thick. AISI 304 stainless steel top.
- Pressed well with large radii, made of 0.8 mm thick AISI 304 stainless steel, diameter 340, height 135 mm.
- Top with 40 mm height in AISI 304 stainless steel, 0.8 mm thick.

### Standard equipment

- Equipped with timed water supply button and tap.
- 1.5" drain and siphon.
- Hot/cold water mixing valve.

### Technical Data

|                   |             |                     |             |
|-------------------|-------------|---------------------|-------------|
| <i>Net Weight</i> | 6 kg        | <i>Gross Weight</i> | 7 kg        |
| <i>Dimensions</i> | 40x40x25 cm | <i>Packing</i>      | 50x41x40 cm |