

EX15BR



REFRIGERATOR -20°C ÷ -10°C GN 2/1 PRE-SET FOR REMOTE COOLING CONNECTION

Refrigerator with internal and external one-piece structure made of AISI 304 stainless steel. Storage chamber equipped with shelf supports in AISI 304 stainless steel, 21 levels. Ventilated cooling system, evaporator positioned outside the refrigerating chamber. Control panel with digital thermometer-thermostat. Electric defrosting. Delivered as standard with: 6 plastified GN 2/1 grids, 6 pairs of AISI 304 stainless steel guides and 3 plastified connecting grids.



REFRIGERATOR -20°C ÷ -10°C GN 2/1 PRE-SET FOR REMOTE COOLING CONNECTION

Refrigerators

<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy Efficiency Class</i>	product are excluded from the European energy classification label according to EU Regulation 2015/1094
<i>LWA dB(A)</i>	20	<i>Net usable volume, lt</i>	1080
<i>Refrigerant/GWP</i>	R452A/2141	<i>Refrigeration power -23,3°C W</i>	1054
<i>Temperature range</i>	-20/-10°C	<i>Volume, gross, lt</i>	1180

Functional features

- Temperature range inside cell: -2°C ÷ +8°C.
- Reliability tested up to + 43°C.
- The appliance is set up for operation with a remote group running with R452a refrigerant fluid.
- This product is equipped with a thermostatic valve and solenoid valve; not supplied: copper pipes, electrical cables for connection to the motor unit.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- Automatic condensation evaporation.
- Easy access to all controls and parts from the control board.
- Microswitch for internal fan stop and lamp switch on when door is open.

Constructional features

- One-piece construction structure made of AISI 304 stainless steel, door inner side and inner ceiling made of special anti-fingerprint steel, inner rounded corners, CFC-free polyurethane insulation.
- Insulation thickness: 75 mm.
- Ventilated refrigeration system through finned evaporator with anti-corrosion treatment, positioned outside the refrigerating chamber means more storage space available.
- Racks made of AISI 304 stainless steel, easily removable, 21 positions rack, 60 mm clearance.
- Doors on AISI 304 stainless steel hinges, equipped with a self-closing device for openings inferior to 90°. Integrated full-height handle with easy grip. Magnetic gasket, easily removable.
- Depth with door open: 1475 mm.
- Lighting through LED lamp with easy access.
- Key-operated lock.
- Stainless steel AISI 304 stainless steel h 150 mm, adjustable in height from 115 to 165 mm.

Standard equipment

- Delivered as standard with: 6 plastified GN 2/1 grids.

Optionals and Accessories

- Cooling unit, temperature recorder, pedal opening, various containers and / or grids.

Technical Data



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 80
web: www.angelopo.com - email: angelopo@angelopo.it

27/02/2024

EX15BR



<i>Working voltage</i>	220V/230V/240V 1N~ / 50÷60 Hz	<i>Net Weight</i>	165 kg
<i>Gross Weight</i>	185 kg	<i>Electric Power</i>	0,82 kW
<i>Dimensions</i>	150x80x204 cm	<i>Packing</i>	154x85,5x207 cm

REFRIGERATOR -20°C ÷ -10°C GN 2/1 PRE-SET FOR REMOTE COOLING CONNECTION **Refrigerators**

