

## FREEZER -20°C ÷ -10°C GN 2/1

Refrigerator with internal and external one-piece structure made of AISI 304 stainless steel. Storage chamber equipped with shelf supports in AISI 304 stainless steel, 21 levels. Ventilated cooling system, evaporator positioned outside the refrigerating chamber. Control panel with digital thermometer-thermostat. Electric defrosting. Each compartment is delivered as standard with: n. 3 pairs of AISI 304 stainless steel guides and n. 3 plastic-coated grids.



Climate class	5 (+40°C, 40% R.H.)	Energy consumption, kWh/24h	6,5
Energy consumption/year, kWh/a	2373	Energy Efficiency Class	D
Energy Efficiency Index	62,96	Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
LWA dB(A)	40	Net usable volume, lt	466
Refrigerant charge, kg	0,1	Refrigerant/GWP	R290/3
Refrigeration power -23,3°C W	453	Temperature range	-20/-10°C
Volume, gross, lt	590		

### Functional features

- Operating temperature: -20°C ÷ -10°C.
- Reliability tested up to + 43°C.
- Power unit with refrigerant fluid R290.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- Automatic condensation evaporation.
- Easy access to all controls and parts from the control board.
- Microswitch for internal fan stop and lamp switch on when door is open.

### Constructional features

- One-piece construction structure made of AISI 304 stainless steel, door inner side and inner ceiling made of special anti-fingerprint steel, inner rounded corners, CFC-free polyurethane insulation.
- Insulation thickness: 75 mm.
- Ventilated refrigeration system through finned evaporator with anti-corrosion treatment, positioned outside the refrigerating chamber means more storage space available.
- Racks made of AISI 304 stainless steel, easily removable, 21 positions rack, 60 mm clearance.
- Doors on AISI 304 stainless steel hinges, equipped with a self-closing device for openings inferior to 90°. Integrated full-height handle with easy grip. Magnetic gasket, easily removable.
- Depth with door open: 1475 mm.
- Lighting through LED lamp with easy access.
- Key-operated lock.
- Stainless steel AISI 304 stainless steel h 150 mm, adjustable in height from 115 to 165 mm.

### Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	120 kg
-----------------	-----------------	------------	--------

## EX7B



Gross Weight	135 kg	Electric Power	0,66 kW
Dimensions	75x80x204 cm	Packing	79x85,5x213 cm

Refrigerators  
FREEZER -20°C ÷ -10°C GN 2/1