

## REFRIGERATOR -2°C ÷ +8°C GN 2/1

Refrigerator with internal and external one-piece structure made of AISI 304 stainless steel. Storage chamber equipped with shelf supports in AISI 304 stainless steel, 21 levels. Ventilated cooling system , evaporator positioned outside the refrigerating chamber. Control panel with digital thermometer-thermostat. Electric defrosting. Each compartment is delivered as standard with: n. 3 pairs of AISI 304 stainless steel guides and n. 3 plastic-coated grids.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy consumption, kWh/24h</i>	1,852
<i>Energy consumption/year, kWh/a</i>	676	<i>Energy Efficiency Class</i>	C
<i>Energy Efficiency Index</i>	49,18	<i>Heavy duty cabinets</i>	This appliance is intended for use in ambient temperatures up to 40 °C
<i>LWA dB(A)</i>	38	<i>Net usable volume, lt</i>	466
<i>Refrigerant charge, kg</i>	0,08	<i>Refrigerant/GWP</i>	R290/3
<i>Refrigeration power at -10°C W</i>	465	<i>Temperature range</i>	-2/+8°C
<i>Volume, gross, lt</i>	590		

### Functional features

- Temperature range inside cell: -2°C ÷ +8°C.
- Reliability tested up to + 43°C.
- Power unit with refrigerant fluid R290.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- Automatic condensation evaporation.
- Easy access to all controls and parts from the control board.
- Microswitch for internal fan stop and lamp switch on when door is open.

### Constructional features

- One-piece construction structure made of AISI 304 stainless steel, door inner side and inner ceiling made of special anti-fingerprint steel, inner rounded corners, CFC-free polyurethane insulation.
- Insulation thickness: 75 mm.
- Ventilated refrigeration system through finned evaporator with anti-corrosion treatment, positioned outside the refrigerating chamber means more storage space available.
- Racks made of AISI 304 stainless steel, easily removable, 21 positions rack, 60 mm clearance.
- Door on AISI 304 stainless steel hinges, easily reversible on site, equipped with a self-closing device for openings inferior to 90°. Integrated full-height handle with easy grip. Magnetic gasket, easily removable.
- Depth with door open: 1475 mm.
- Lighting through LED lamp with easy access.
- Key-operated lock.
- Stainless steel AISI 304 stainless steel h 150 mm, adjustable in height from 115 to 165 mm.

### Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	113 kg
------------------------	-----------------	-------------------	--------



# EX7L



<i>Gross Weight</i>	128 kg	<i>Electric Power</i>	0,21 kW
<i>Dimensions</i>	75x80x204 cm	<i>Packing</i>	79x85,5x213 cm

REFRIGERATOR -2°C ÷ +8°C GN 2/1  
Refrigerators



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90  
web: [www.angelopo.com](http://www.angelopo.com) - email: [angelopo@angelopo.it](mailto:angelopo@angelopo.it) 20/06/2024