

**REFRIGERATOR -2°C ÷ +8°C / -20°C ÷ -10°C  
GN 2/1**

Refrigerator with internal and external one-piece structure made of AISI 304 stainless steel. Storage chamber equipped with shelf supports in AISI 304 stainless steel, 21 levels. Ventilated cooling system, evaporator positioned inside the refrigerating chamber. Control panel with digital thermometer-thermostat. Electric defrosting. Each compartment is delivered as standard with: n. 2 pairs of AISI 304 stainless steel guides and n. 2 plastic-coated grids.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy Efficiency Class</i>	product are excluded from the European energy classification label according to EU Regulation 2015/1094
<i>LWA dB(A)</i>	51	<i>Net usable volume, lt</i>	289
<i>Refrigerant charge, kg</i>	0,06+0,08	<i>Refrigerant/GWP</i>	R290/3
<i>Refrigeration power -23,3°C W</i>	611	<i>Refrigeration power at -10°C W</i>	345
<i>Temperature range</i>	-2/+8 ÷ -20/-10	<i>Volume, gross, lt</i>	535

**Functional features**

- Temperature range inside cell: -2°C ÷ +8°C / -20°C ÷ -10°C
- Separate compartments.
- Reliability tested up to + 43°C.
- 2 power units with refrigerant fluid R290.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- Automatic condensation evaporation.
- Easy access to all controls and parts from the control board.
- Microswitch for internal fan stop and lamp switch on when door is open.

**Constructional features**

- One-piece construction structure made of AISI 304 stainless steel, door inner side and inner ceiling made of special anti-fingerprint steel, inner rounded corners, CFC-free polyurethane insulation.
- Insulation thickness: 75 mm.
- Ventilated refrigeration system through finned evaporator with anti-corrosion treatment, positioned inside the refrigerating chamber. means more storage space available.
- Racks made of AISI 304 stainless steel, easily removable, 7+7 positions rack, 60 mm clearance.
- Doors on AISI 304 stainless steel hinges, equipped with a self-closing device for openings inferior to 90°. Integrated full-height handle with easy grip. Magnetic gasket, easily removable.
- Depth with door open: 1475 mm.
- Lighting through lamp with easy access.
- Key-operated lock.
- Stainless steel AISI 304 stainless steel h 150 mm, adjustable in height from 115 to 165 mm.

**Standard equipment**

- Each compartment is delivered as standard with: n. 2 GN 2/1 plastic-coated grids and n. 2 pairs of AISI 304 stainless steel guides.

**Optional**

- Temperature recorder, pedal opening, various containers and / or grids.

# EX7LB



## Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	162 kg
<i>Gross Weight</i>	177 kg	<i>Electric Power</i>	0,75 kW
<i>Dimensions</i>	75x81,5x204 cm	<i>Packing</i>	79x85,5x207 cm

REFRIGERATOR -2°C ÷ +8°C / -20°C ÷ -10°C GN 2/1

Refrigerators