

EX7LR



REFRIGERATOR -2°C ÷ +8°C GN 2/1 PRE-SET FOR REMOTE COOLING CONNECTION



Refrigerator with internal and external one-piece structure made of AISI 304 stainless steel. Storage chamber equipped with shelf supports in AISI 304 stainless steel, 21 levels. Ventilated cooling system, evaporator positioned outside the refrigerating chamber. Control panel with digital thermometer-thermostat. Electric defrosting. Each compartment is delivered as standard with: n. 3 pairs of AISI 304 stainless steel guides and n. 3 plastic-coated grids.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy Efficiency Class</i>	product are excluded from the European energy classification label according to EU Regulation 2015/1094
<i>LWA dB(A)</i>	20	<i>Net usable volume, lt</i>	466
<i>Refrigerant/GWP</i>	R134a/1430	<i>Refrigeration power at -10°C W</i>	286
<i>Temperature range</i>	-2/+8°C	<i>Volume, gross, lt</i>	590

Functional features

- Temperature range inside cell: -2°C ÷ +8°C.
- Reliability tested up to + 43°C.
- The appliance is set up for operation with a remote group running with R134a refrigerant fluid.
- This product is equipped with a thermostatic valve and solenoid valve; not supplied: copper pipes, electrical cables for connection to the motor unit.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Automatic defrosting system by heating elements.
- Automatic condensation evaporation.
- Easy access to all controls and parts from the control board.
- Microswitch for internal fan stop and lamp switch on when door is open.

Constructional features

- One-piece construction structure made of AISI 304 stainless steel, door inner side and inner ceiling made of special anti-fingerprint steel, inner rounded corners, CFC-free polyurethane insulation.
- Insulation thickness: 75 mm.
- Ventilated refrigeration system through finned evaporator with anti-corrosion treatment, positioned outside the refrigerating chamber means more storage space available.
- Racks made of AISI 304 stainless steel, easily removable, 21 positions rack, 60 mm clearance.
- Duct panel improving temperature distribution inside refrigeration chamber and ensuring that it is correct even with poorly distributed loads.
- Door on AISI 304 stainless steel hinges, easily reversible on site, equipped with a self-closing device for openings inferior to 90°. Integrated full-height handle with easy grip. Magnetic gasket, easily removable.
- Depth with door open: 1475 mm.
- Lighting through LED lamp with easy access.
- Key-operated lock.
- Stainless steel AISI 304 stainless steel h 150 mm, adjustable in height from 115 to 165 mm.

Standard equipment

- Delivered as standard with: 3 plastified GN 2/1 grids.

Optionals and Accessories

- Cooling unit, temperature recorder, pedal opening, various containers and / or grids.



EX7LR



Technical Data

<i>Working voltage</i>	220V/230V/240V 1N~ / 50÷60 Hz	<i>Net Weight</i>	95 kg
<i>Gross Weight</i>	110 kg	<i>Electric Power</i>	0,7 kW
<i>Dimensions</i>	75x80x204 cm	<i>Packing</i>	79x85,5x213 cm

REFRIGERATOR -2°C ÷ +8°C GN 2/1 PRE-SET FOR REMOTE COOLING CONNECTION Refrigerators

