

REFRIGERATED DISPLAY UNIT -25 ÷ -15°C COLOR GREY

Vertical refrigerated display cabinet. Display cabinet made in in hardened double glazing, silk-screened exterior, lower structure in special steel on wheels. Color: grey. Lighting through LED lights. Nr. 5 evaporating grids and 1 support shelf. Control panel with electronic PCB, capacitive keys, HACCP alarms. Static refrigeration through evaporating grids, electric element against condensation on the windows, manual defrosting.



Climate class	4 (+30°C, 55% R.H.)	Energy consumption/year, kW/h	5684
Energy Efficiency Class	C	Method for energy consumption	EN 23953
Refrigeration power -23,3°C W	962	Temperature ranges, °C	-25/-15
Volume, gross, lt	324		

Functional features

- Operating temperature: -25°C ÷ -15°C.
- Relative humidity: 75%.
- Power unit with refrigerant fluid R290.
- Electronic control board with HACCP alarm signalling.
- Manual defrosting.
- Snap removable front dashboard for compressor cleaning operations.

Constructional features

- Display cabinet made entirely of hardened double glazing, with grey silk-screened glass. Lower structure in grey special steel.
- Display compartment with 5 evaporating grids and 1 shelf. Size of each grid: cm 45 x 46.
- Door with integrated full-height handle, easy to take, not reversible on site. Easily removable magnetic gasket.
- Static refrigeration through evaporating grids.
- Anti-condensation electric elements on the glasses.
- Interior lighting in refrigerated display through LED bars, front on the back of the door.
- Wheels and feet integrated in the lower structure (4).
- Installation allowed to an altitude up to 800 metres above sea level.

Standard equipment

- 5 evaporating grids and 1 support shelf.

Optional

- 5 tempered glass shelves

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	197 kg
Gross Weight	222 kg	Electric Power	0,85 kW
Dimensions	60x64,5x184 cm	Packing	74x76x202 cm