

WALL MOUNTED PACKAGED UNIT 0/+5°C FOR COLD ROOM MC 8 ÷ 10

Refrigerant unit for cold rooms. Self-supporting casing in zinc-plated metal sheet, which is coated with epoxy powder, hermetic compressor. Control panel with electronic PCB that can be programmed. Refrigerant fluid R290. Automatic defrosting by hot gas. Installation: wall-mounted.



<i>Air throw m</i>	6,5	<i>For cold rooms from ÷ to</i>	8 ÷ 10
<i>Operating temperature</i>	0/+5°C	<i>Product fitting up</i>	Wall mounted
<i>Refrigerant charge (kg)</i>	0.15 (<=each circuit)	<i>Refrigerant/GWP</i>	R290/3
<i>Refrigeration power</i>	1373 W (at 0°C and RT +43°C)		

Functional features

- Operating temperature: 0°C ÷ +5°C.
- Reliability tested up to + 43°C room temperature.
- Refrigerant fluid R290.
- No. of circuits for refrigerant fluid: 1
- Front control panel easy removable in order to guarantee an easy access to the components and a fast maintenance intervention.
- Electronic PCB that can be programmed.
- Electronic control panel.
- Condensation by air.
- Automatic defrosting by hot gas.
- Evaporation tray on board the machine with overflow.

Constructional features

- Self-supporting casing in zinc-plated metal sheet, which is coated with epoxy powder.
- Hermetic compressor with thermal motor protection.
- Heat exchangers with copper and aluminium blocks.

Safety equipment and approvals

- Security pressure switch.

Standard equipment

- LED light with 5m cable.
- Door micro switch with 2.5 m long cable.
- Power supply 2.5 m cable.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	67 kg
<i>Gross Weight</i>	100 kg	<i>Electric Power</i>	0,99 kW
<i>Dimensions</i>	68x98x83 cm	<i>Packing</i>	77x107x98 cm

WALL MOUNTED PACKAGED UNIT 0/+5°C FOR COLD ROOM MC 8 ÷ 10

Cold rooms