GMP4B

WALL MOUNTED PACKAGED UNIT -18/-20°C FOR COLD ROOM MC 3.1 ÷ 4.1

Rrefrigerant unit for cold rooms. Self-supporting casing in zinc-plated metal sheet, which is coated with epoxy powder, hermetic compressor. Control panel with electronic PCB that can be programmed. Refrigerant fluid R290. Automatic defrosting by hot gas. Installation: wall-mounted.

CE

Air throw m	6,5	*For cold rooms from ÷ to*	3,1 ÷ 4,1
Operating temperature	-18°C/-20°C	*Product fitting up*	Wall mounted
Refrigerant charge (kg)	0.15 (<= each circuit)	*Refrigerant/GWP*	R290/3
Refrigeration power	588 W (at -20°C and RT +43°C)		

Functional features

- Operating temperature: 0°C ÷ +5°C.
- Reliability tested up to + 43°C room temperature.
- Refrigerant fluid R290.
- No. of circuits for refrigerant fluid: 1
- Front control panel easy removable in order to guarantee an easy access to the components and a fast maintenance intervention.
- Electronic PCB that can be programmed.
- Electronic control panel.
- Condensation by air.
- Automatic defrosting by hot gas.
- Evaporation tray on board the machine with overflow.

Constructional features

- Self-supporting casing in zinc-plated metal sheet, which is coated with epoxy powder.
- Hermetic compressor with thermal motor protection.
- Heat exchangers with copper and aluminium blocks.

Safety equipment and approvals

- Security pressure switch.

Standard equipment

- LED light with 5m cable.
- Door micro switch with 2.5 m long cable.
- Power supply 2.5 m cable.
- Door heater 2.5 m cable.

Technical Data

Working voltage	230V 1N~ / 50Hz	*Net Weight*	45 kg
Gross Weight	56 kg	*Electric Power*	0,69 kW
Dimensions	43x88x73 cm	*Packing*	50x97x89 cm