

## DISHWASHER 40 BASKETS/H BASKET 50x50 CM

Dishwasher with stainless steel structure, bonded double wall sides, double wall door, built-in rinse aid dispenser. Soft-touch control panel with LCD screen, electronic board. 3 washing programs 60"-120"-150", continuous washing. Included: 1 basket for 16 plates, 1 flat basket, 1 cutlery insert.



<i>Basket dimensions cm</i>	50 x 50	<i>Boiler</i>	Pressurized
<i>Door / hood construction</i>	Double wall	<i>Door / hood opening cm</i>	36,5
<i>Glasses/plates max H cm</i>	32,5 / 36,5	<i>Production baskets/h</i>	40
<i>Rinse aid dispenser</i>	supplied as standard	<i>Sides construction</i>	Bonded double wall
<i>SoftTouch control panel</i>	LED display	<i>Water consumption per cycle/lt</i>	2,3

### Functional features

- Basket dimensions: 50 x 50 cm.
- Useful door clearance: 36.5 cm.
- Maximum height of objects (glasses / plates): 32.5 cm / 36.5 cm.
- Productivity: 40 baskets/h.
- Washing temperature: 60°C.
- Rinse temperature: 80°C.
- Water consumption per cycle: 2.3 lt.
- Built-in rinse aid dispenser.
- Soft-touch control panel with electronic board, 2 LED displays: 3 washing programs of 90"-120"-150", continuous washing, washing and rinsing temperature selection, self-cleaning program.
- Display of the temperature in the tank and the boiler.
- THERMOSTOP function: controls the correct rinsing temperature in the boiler, ensuring perfect hygiene and drying.
- ENERGY SAVING system: reduces the boiler temperature when the dishwasher is not washing. It reduces energy consumption and the formation of limescale in the boiler.
- SUPPLY: water 15-60°C; hardness 2-8°F; pressure 200-400 kPa.

### Constructional features

- Dishwasher made in stainless steel, bonded double wall sides.
- Double-wall door, bound by hinges and cushioned.
- Pressed basket runners.
- AISI 304 stainless steel tank with pressed bottom and inclined towards the drain; composite material filter; capacity 20 lt; tank resistance: 2.1 kW.
- Pressurized boiler; capacity 6 lt; resistance 6 kW.
- Double flow washing pump 0.5 kW powered.
- Lower washing arms in stainless steel.
- Lower rinse arms in stainless steel.
- Discharge system via overflow.
- Sound pressure dB (A): 59.3.

### Safety equipment and approvals

- CE approvals in respect of all directives and regulations.
- Boiler and tank with safety thermostat.
- IPX4 protection rating.

### Standard equipment



# KLE50



- Built-in rinse aid dispenser.
- n. 1 basket for 16 plates Ø 24 cm (KEBPIN16).
- n.1 flat basket 50x50 cm (KEBFLA).
- n.1 insert for cutlery (CPP).
- Power cable, inlet hose and drain hose.

## Optionals and Accessories

- Level switch for external tank, drain pump, detergent dispenser, closed and open frame, various baskets.

## Technical Data

<i>Working voltage</i>	400V 3N~ / 50Hz	<i>Net Weight</i>	54 kg
<i>Gross Weight</i>	60 kg	<i>Electric Power</i>	6,5 kW
<i>Dimensions</i>	57,5x60,5x82 cm	<i>Packing</i>	69x67x98 cm

Serie KLE  
DISHWASHER 40 BASKETS/H BASKET 50x50 CM