

DISHWASHER 40 BASKETS/H BASKET 50x50 CM WITH DRAIN PUMP

Dishwasher with stainless steel structure, bonded double wall sides, double wall door, built-in rinse aid dispenser. Soft-touch control panel with LCD screen, electronic board. 3 washing programs 60"-120"-150", continuous washing. Drain pump and detergent dispenser. Included: 1 basket for 16 plates, 1 flat basket, 1 cutlery insert.



Basket dimensions cm	50 x 50	Blue Water System	yes
Boiler	Pressurized	Detergent dispenser	supplied as standard
Door / hood construction	Double wall	Door / hood opening cm	36,5
Drain pump	supplied as standard	Glasses/plates max H cm	32,5 / 36,5
Production baskets/h	40	Rinse aid dispenser	supplied as standard
Sides construction	Bonded double wall	SoftTouch control panel	LED display
Water consumption per cycle/lt	2,3		

Functional features

- Basket dimensions: 50 x 50 cm.
- Useful door clearance: 36.5 cm.
- Maximum height of objects (glasses / plates): 32.5 cm / 36.5 cm.
- Productivity: 40 baskets/h.
- Washing temperature: 60°C.
- Rinse temperature: 80°C.
- Water consumption per cycle: 2.3 lt.
- Built-in rinse aid and detergent dispensers.
- Soft-touch control panel with electronic board, 2 LED displays: 3 washing programs of 90"-120"-150", continuous washing, washing and rinsing temperature selection, self-cleaning program, quick drain program.
- Display of the temperature in the tank and the boiler.
- SOFT-START function: the pump start system with electronic soft start allows a gentle wash also suitable for treating delicate objects such as crystal glasses.
- THERMOSTOP function: controls the correct rinsing temperature in the boiler, ensuring perfect hygiene and drying.
- ENERGY SAVING system: reduces the boiler temperature when the dishwasher is not washing. It reduces energy consumption and the formation of limescale in the boiler.
- SUPPLY: water 15-60°C; hardness 2-8°F; pressure 200-400 kPa.

Constructional features

- Dishwasher made in stainless steel, bonded double wall sides.
- Double-wall door, bound by hinges and cushioned.
- Pressed basket runners.
- AISI 304 stainless steel tank with pressed bottom and inclined towards the drain; composite material filter; capacity 20 lt; tank resistance: 2.1 kW.
- Pressurized boiler; capacity 6 lt; resistance 6 kW.
- Double flow washing pump 0.5 kW powered.
- Drain pump.
- Lower washing arms in stainless steel.
- Lower rinse arms in stainless steel.
- Discharge system by pump.
- Sound pressure dB (A): 59.3.

KLE50PD



Safety equipment and approvals

- CE approvals in respect of all directives and regulations.
- Boiler and tank with safety thermostat.
- IPX4 protection rating.

Standard equipment

- Built-in rinse aid and detergent dispensers.
- n. 1 basket for 16 plates Ø 24 cm (KEBPIN16).
- n.1 flat basket 50x50 cm (KEBFLA).
- n.1 insert for cutlery (CPP).
- Power cable, inlet hose and drain hose.

Optionals and Accessories

- Level switch for external tank, closed and open frame, various baskets.

Technical Data

Working voltage	400V 3N~ / 50Hz	Net Weight	54 kg
Gross Weight	60 kg	Electric Power	6,5 kW
Dimensions	57,5x60,5x82 cm	Packing	69x67x98 cm

DISHWASHER 40 BASKETS/H BASKET 50x50 CM WITH DRAIN PUMP
Serie KLE