

## DISHWASHER 60 BASKETS/H BASKET 50x50 - 50x60 CM WITH DRAIN PUMP

Dishwasher with stainless steel structure, bonded double wall sides, double wall door, built-in rinse aid dispenser. Soft-touch control panel with LCD screen, electronic board. 3 washing programs 60"-120"-150", continuous washing. Drain pump and detergent dispenser. Included: 1 basket 50x60 for 22 dishes, 1 flat basket, 1 cutlery insert.



<i>Basket dimensions cm</i>	50 x 50 - 50 x 60	<i>Blue Water System</i>	yes
<i>Boiler</i>	Pressurized	<i>Detergent dispenser</i>	supplied as standard
<i>Door / hood construction</i>	Double wall	<i>Door / hood opening cm</i>	40
<i>Drain pump</i>	supplied as standard	<i>Glasses/plates max H cm</i>	37,5 / 41
<i>Production baskets/h</i>	60	<i>Rinse aid dispenser</i>	supplied as standard
<i>Sides construction</i>	Bonded double wall	<i>SoftTouch control panel</i>	LED display
<i>Useful for 60x40 containers</i>	yes	<i>Useful for GN / EN containers</i>	yes
<i>Water consumption per cycle/lt</i>	2,5		

### Functional features

- Basket dimensions: 50 x 50 / 50 x 60 cm.
- Useful door clearance: 40 cm.
- Maximum height of objects (glasses / plates): 37.5 cm / 41 cm.
- Productivity: 60 baskets/h.
- Washing temperature: 60°C.
- Rinse temperature: 80°C.
- Water consumption per cycle: 2.5 lt.
- Built-in rinse aid and detergent dispensers.
- Soft-touch control panel with electronic board, 2 LED displays: 3 washing programs of 60"-120"-150", continuous washing, washing and rinsing temperature selection, self-cleaning program, quick drain program.
- Display of the temperature in the tank and the boiler.
- SOFT-START function: the pump start system with electronic soft start allows a gentle wash also suitable for treating delicate objects such as crystal glasses.
- THERMOSTOP function: controls the correct rinsing temperature in the boiler, ensuring perfect hygiene and drying.
- ENERGY SAVING system: reduces the boiler temperature when the dishwasher is not washing. It reduces energy consumption and the formation of limescale in the boiler.
- SUPPLY: water 15-60°C; hardness 2-8°F; pressure 200-400 kPa.

### Constructional features

- Dishwasher made in stainless steel, bonded double wall sides.
- Double-wall door, bound by hinges and cushioned.
- AISI 304 stainless steel tank with pressed bottom and inclined towards the drain; stainless steel filter; capacity 22 lt; tank resistance: 2.1 kW.
- Pressurized boiler; capacity 6 lt; resistance 6 kW.
- Double flow washing pump 0.7 kW powered.
- Drain pump.
- Lower washing arms in stainless steel.
- Lower rinse arms in stainless steel.

DISHWASHER 60 BASKETS/H BASKET 50x50 - 50x60 CM WITH DRAIN PUMP

Serie KLE

# KLE80PD



- Discharge system by pump.
- Sound pressure dB (A): 60.

---

## Safety equipment and approvals

- CE approvals in respect of all directives and regulations.
- Boiler and tank with safety thermostat.
- IPX4 protection rating.

---

## Standard equipment

- Built-in rinse aid and detergent dispensers.
- n. 1 basket 50x60 cm 22 plates Ø 29 cm (KE56B1).
- n.1 flat basket 50x50 cm (KEBFLA).
- n.1 insert for cutlery (CPP).
- Power cable, inlet hose and drain hose.

---

## Optionals and Accessories

- Level switch for external tank, various baskets.

---

## Technical Data

<i>Working voltage</i>	400V 3N~ / 50Hz	<i>Net Weight</i>	66 kg
<i>Gross Weight</i>	72 kg	<i>Electric Power</i>	6,7 kW
<i>Dimensions</i>	57,5x70x129 cm	<i>Packing</i>	78x67x125 cm

DISHWASHER 60 BASKETS/H BASKET 50X50 - 50X60 CM WITH DRAIN PUMP

Serie KLE

