

HOOD DISHWASHER 60 BASKETS/H 50x50 CM WITH DRAIN PUMP

Lavastoviglie con struttura in acciaio inox, fianchi a doppia parete stratificata, capote a parete singola, dosatore di brillantante incorporato. Soft-touch control panel with LCD screen, electronic board. 3 washing programs 60"-120 "-150", continuous washing. Drain pump and detergent dispenser. Included: 1 basket for 16 plates, 1 flat basket, 1 cutlery insert.



<i>Air-gap break tank</i>	yes	<i>Basket dimensions cm</i>	50 x 50
<i>Blue Water System</i>	yes	<i>Boiler</i>	Atmospheric
<i>Detergent dispenser</i>	supplied as standard	<i>Door / hood construction</i>	Single wall
<i>Door / hood opening cm</i>	45	<i>Drain pump</i>	supplied as standard
<i>Glasses/plates max H cm</i>	42,5 / 44	<i>Production baskets/h</i>	60
<i>Rinse aid dispenser</i>	supplied as standard	<i>Sides construction</i>	Bonded double wall
<i>SoftTouch control panel</i>	LED display	<i>Useful for GN / EN containers</i>	yes
<i>Water consumption per cycle/lt</i>	2,3		

Functional features

- Basket dimensions: 50 x 50 cm.
- Useful door clearance: 45 cm.
- Maximum height of objects (glasses / plates): 42.5 cm / 44 cm.
- Productivity: 60 baskets/h.
- Washing temperature: 60°C.
- Rinse temperature: 80°C.
- Water consumption per cycle: 2.3 lt.
- Built-in rinse aid and detergent dispensers.
- Soft-touch control panel with electronic board, 2 LED displays: 3 washing programs of 60"-120"-150", continuous washing, washing and rinsing temperature selection, self-cleaning program, quick drain program.
- Display of the temperature in the tank and the boiler.
- SOFT-START function: the pump start system with electronic soft start allows a gentle wash also suitable for treating delicate objects such as crystal glasses.
- THERMOSTOP function: controls the correct rinsing temperature in the boiler, ensuring perfect hygiene and drying.
- ATMOSPHERIC BOILER: guarantees rinsing at constant temperature and pressure, eliminating the drawbacks of the variation in mains water pressure and temperature in the rinsing phase (even of 20-30°C) of traditional systems; it allows lower water consumption and lower temperatures.
- ENERGY SAVING system: reduces the boiler temperature when the dishwasher is not washing. It reduces energy consumption and the formation of limescale in the boiler.
- SUPPLY: water 15-60°C; hardness 2-8°F; pressure 200-400 kPa.

Constructional features

- Lavastoviglie realizzata in acciaio inox, fianchi a doppia parete stratificata, piedini regolabili.
- Single wall hood in AISI 304 stainless steel, handle for lifting.
- AISI 304 stainless steel tank with pressed bottom and inclined towards the drain; composite material filter; capacity 20 lt; tank resistance: 2.5 kW.
- Atmospheric boiler; capacity 6 liters; heat resistance 8 kW.
- Double flow washing pump 0.7 kW powered.

KLE90PD



- Drain pump.
- Stainless steel washing arms.
- Stainless steel rinse arms.
- Discharge system by pump.
- Sound pressure dB (A): 60.4.

Safety equipment and approvals

- CE approvals in respect of all directives and regulations.
- Boiler and tank with safety thermostat.
- Break tank (air gap) standard supplied to guarantee of no return of wash water into the water supply.
- IPX4 protection rating.

Standard equipment

- Built-in rinse aid and detergent dispensers.
- n. 1 basket for 16 plates Ø 24 cm (KEBPIN16).
- n.1 flat basket 50x50 cm (KEBFLA).
- n.1 insert for cutlery (CPP).
- Power cable, inlet hose and drain hose.

Optionals and Accessories

- Level switch for external tank, drain pump, detergent dispenser, various baskets, entry / exit tables.

Technical Data

<i>Working voltage</i>	400V 3N~ / 50Hz	<i>Net Weight</i>	90 kg
<i>Gross Weight</i>	100 kg	<i>Electric Power</i>	8,7 kW
<i>Dimensions</i>	72,4x81,8x152,9 cm	<i>Packing</i>	76x84x152 cm

HOOD DISHWASHER 60 BASKETS/H 50x50 CM WITH DRAIN PUMP
Serie KLE