

## GLASS WASHER 30 BASKETS/H BASKET 35x35 CM

Glass washer with stainless steel structure, single wall sides, double wall door, built-in rinse aid dispenser. Soft-touch control panel with LCD screen, electronic board. 1 washing program 120". Included: 2 flat baskets and 1 cutlery insert.



<i>Basket dimensions cm</i>	35 x 35	<i>Boiler</i>	Pressurized
<i>Door / hood construction</i>	Double wall	<i>Door / hood opening cm</i>	26
<i>Glasses/plates max H cm</i>	24 / n.a.	<i>Production baskets/h</i>	30
<i>Rinse aid dispenser</i>	supplied as standard	<i>Sides construction</i>	Single wall
<i>SoftTouch control panel</i>	LED display	<i>Water consumption per cycle/lt</i>	1,8

### Functional features

- Basket dimensions: 35 x 35 cm.
- Useful door clearance: 26 cm.
- Maximum height of objects (glasses / plates): 24 cm / -.
- Productivity: 30 baskets/h.
- Washing temperature: 60°C.
- Rinse temperature: 65°C.
- Water consumption per cycle: 1.8 lt.
- Built-in rinse aid dispenser.
- Soft-touch control panel with electronic board, 2 LED displays: 1 washing program of 120', washing and rinsing temperature selection.
- Display of the temperature in the tank and the boiler.
- THERMOSTOP function: controls the correct rinsing temperature in the boiler, ensuring perfect hygiene and drying.
- ENERGY SAVING system: reduces the boiler temperature when the dishwasher is not washing. It reduces energy consumption and the formation of limescale in the boiler.
- SUPPLY: water 50-60°C; hardness 2-8°F; pressure 200-400 kPa.

### Constructional features

- Dishwasher made of stainless steel with single wall structure.
- Double-wall door, bound by hinges.
- Welded basket runners.
- AISI 304 stainless steel tank with pressed bottom and inclined towards the drain; capacity 7 lt; tank resistance: 0.6 kW.
- Pressurized boiler; capacity 2.6 lt; resistance 2.6 kW.
- Wash pump 0.15 kW.
- Washing arms in composite material.
- Rinsing arms in composite material.
- Discharge system via overflow.
- Sound pressure dB (A): 48.3.

### Safety equipment and approvals

- CE approvals in respect of all directives and regulations.
- Boiler and tank with safety thermostat.
- IPX4 protection rating.

### Standard equipment

- Built-in rinse aid dispenser.

# KNE35



- n. 2 flat baskets 35x35 cm (C35KNE35).
- n.1 insert for cutlery (CPP).
- Power cable, inlet hose and drain hose.

## Options and Accessories

- Level switch for external tank, drain pump, detergent dispenser, round basket and adapter.

## Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	27 kg
Gross Weight	30 kg	Electric Power	3,4 kW
Dimensions	40,1x49x59,5 cm	Packing	59x47x75 cm

GLASS WASHER 30 BASKETS/H BASKET 35x35 CM  
Serie KNE