

UTENSILWASHER 30 BASKETS/H 55x61 CM

Utensilwasher with spaced double wall stainless steel structure, double wall door, detergent and rinse aid dispensers incorporated. Soft-touch control panel with LCD screen, electronic board. 4 washing programs 120"-240"-360", continuous washing, self-cleaning program. Delivered with: 1 steel wire basket. The appliance complies with Industry 4.0 regulations if connected to the LAVWI accessory.



<i>Basket dimensions cm</i>	55 x 61	<i>Boiler</i>	Pressurizzato
<i>Capacity EU 40x60 h 4 cm</i>	8	<i>Capacity EU 80x60 h 4 cm</i>	5
<i>Capacity GN 1/1 h 4 cm</i>	8	<i>Capacity GN 2/1 h 4 cm</i>	8
<i>Detergent dispenser</i>	supplied as standard	<i>Door / hood construction</i>	Double wall
<i>Door / hood opening cm</i>	85	<i>Flanks construction</i>	Spaced double wall
<i>Production baskets/h</i>	30	<i>Rinse aid dispenser</i>	supplied as standard
<i>SoftTouch control panel</i>	LED display	<i>Water consumption per cycle/lt</i>	3

Functional features

- Basket dimensions: 55 x 61 cm.
- Useful door clearance: 85 cm.
- Maximum height of objects: 85 cm.
- Productivity: 30 baskets/h.
- Capacity of GN 1/1 h = 4 cm containers: 8
- Capacity of GN 2/1 h = 4 cm containers: 8
- Capacity of 60 x 40 h = 4 cm containers: 8
- Capacity of 60 x 80 h = 4 cm containers: 5
- Washing temperature: 60-65°C.
- Rinse temperature: 80-85°C.
- Water consumption per cycle: 3 lt.
- Built-in rinse aid and detergent dispensers.
- Soft-touch control panel with electronic board, 2 LED displays: 4 washing programs of 120"-240"-360"-600", continuous washing, self-cleaning program, quick drain program, washing and rinsing temperature selection.
- Display of the temperature in the tank and the boiler.
- THERMOSTOP function: controls the correct rinsing temperature in the boiler, ensuring perfect hygiene and drying.
- ENERGY SAVING system: reduces the boiler temperature when the dishwasher is not washing. It reduces energy consumption and the formation of limescale in the boiler.
- SUPPLY: water 15-60°C; hardness 2-8°F; pressure 200-400 kPa.
- The appliance complies with Industry 4.0 regulations if connected to the LAVWI accessory.

Constructional features

- Utensilwasher with spaced double wall stainless steel structure, adjustable feet.
- Double-wall door, bound by hinges.
- Fully pressed AISI 304 stainless steel tank, stainless steel filter; capacity 37 lt; tank resistance: 3 kW.
- Pressurized boiler; resistance 6 kW.
- Double flow washing pump 1.5 kW powered.
- Stainless steel washing arms.
- Stainless steel rinse arms.
- Discharge system via overflow.
- Sound pressure dB (A): 67.4.

LPE151



Safety equipment and approvals

- CE approvals in respect of all directives and regulations.
- Boiler and tank with safety thermostat.
- IPX4 protection rating.

Standard equipment

- Built-in rinse aid and detergent dispensers.
- n. 1 stainless steel wire basket 50 x 61 cm.
- Power cable, inlet hose and drain hose.

Optional

- Level switch for detergent tanks, various baskets.
- LAVWI remote connection device for the compliance with Industry 4.0 regulations.

Technical Data

<i>Working voltage</i>	400V 3N~ / 50Hz	<i>Net Weight</i>	143 kg
<i>Gross Weight</i>	153 kg	<i>Electric Power</i>	7,5 kW
<i>Dimensions</i>	72x78x224,3 cm	<i>Packing</i>	87x89x220 cm

UTENSILWASHER 30 BASKETS/H 55x61 CM
Serie LPE

