

HEATED CUPBOARD BOTH SIDE SLIDING DOORS

AISI 304 stainless steel top 54 mm h with satin finish 12/10 mm thickness. Sound deadening waterproof panel underneath. AISI 304 stainless steel free-standing structure with satin finish, with sliding doors with double walled sandwich panel structure, middle shelf reinforced by omega. Ventilated heating with thermostat +30/+90°C. Double side opening. Height-adjustable stainless steel feet.



<i>Heating system</i>	yes	<i>Opening on two fronts</i>	yes
<i>Worktop without rear splashbac</i>	yes		

Functional features

- Sturdiness of the worktop due to the particular construction and use of AISI 304 stainless steel sheet, thickness 12/10 mm.
- Hygiene ensured by the materials used and by the totally "closed" structure of the worktop.
- Ergonomics, offering a standard height of 90 cm from the floor.
- Easy cleaning ensured by the construction of the rear splashback made in one piece with the top.
- Height-adjustable stainless steel feet for leveling on the floor, equipped with a thermosetting plastic sole.
- Capacity in Ø 23 cm plates on the intermediate shelf: 324.
- Maximum load per shelf with evenly distributed load: 110 kg.
- Doors opening on two sides.

Constructional features

- 54 mm high AISI 304 stainless steel worktop 1.2 mm thick with waterproof sound-absorbing panel.
- Self-supporting cabinet made entirely on sides, back, bottom and door in satin-finished and cold-bent AISI 304 stainless steel.
- Sliding doors, sliding on upper guides, double-skinned. Handle obtained by folding in a single piece with the door.
- Middle shelf that can be positioned in different heights made of AISI 304 stainless steel, with omega reinforcement.
- Stainless steel feet with plastic soles, adjustable for floor leveling, height 150 mm (max height 180 mm).

Safety equipment and approvals

- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).

Optionals and Accessories

- The cabinet can be fitted with casters.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50 ÷ 60Hz	<i>Net Weight</i>	75 kg
<i>Gross Weight</i>	80 kg	<i>Electric Power</i>	2 kW
<i>Dimensions</i>	100x70x90 cm	<i>Packing</i>	105x72x105 cm