

COLD ROOM THICKNESS PANEL 10 CM, INTERNAL HEIGHT 243 CM, 6,1 CBM WITH FLOOR

Plastified panels; thickness 10 cm; insulation in expanded polyurethane without using CFC and HCFC, density 40Kg / m³. DOOR - Useful opening cm 70x190h, hinged to the right and positioned on the longer side of the cold room. Semi-recessed door, overhang 4 cm. Round corner elements, both internally and externally. External handle with key and internal security release. With pedestrian non-slip floor. HACCP certification.



Door opening	70x190 cm	Floor	Yes
Inside height cm	243 cm	Panel thickness	10 cm
Precise load - floor	100 Kg	Temperature range	+5/-20°C

Functional features

- Key-lock and internal security release.
- DOOR - Useful light cm 70x190h, opening from left to right, positioned on the longer side of the cold room.
- Semi-recessed door, overhang 4 cm; advantage of less space outside, less volume to cool at the same flow rate and better seal thanks to the more sealant joint and to the larger magnetic gasket..
- Model without floor.

Constructional features

- Insulation in polyurethane without CFC and HCFC 100 mm thickness, polyurethane insulation density 38/40 kg / m³; K = 0.208 W / m²K.
- Modular prefabricated panels made from food-approved, non-toxic plastic-coated plate.
- Fixing: with two-point fasteners with alignment system.
- Corner units: non-toxic plastic-coated plate cladding, polyurethane insulation, rounded on inside and outside.
- Patented panel fastening system that assures assembly speed and tightness guarantee.
- HACCP certification: the chamber is compliant with the HACCP International standards.

Technical Data

Net Weight	340 kg	Gross Weight	370 kg
Dimensions	223x143x263 cm	Packing	245x125x122 cm

COLD ROOM THICKNESS PANEL 10 CM, INTERNAL HEIGHT 243 CM, 6,1 CBM WITH FLOOR

Cold rooms