

COLD ROOM THICKNESS PANEL 6 CM, INTERNAL HEIGHT 203 CM, 8,4 CBM WITH FLOOR

Plastified panels; thickness 6 cm; insulation in expanded polyurethane without using CFC and HCFC, density 40Kg / m³. DOOR - Useful opening cm 70x190h, hinged to the right and positioned on the longer side of the cold room. Semi-recessed door, overhang 4 cm. Round corner elements, both internally and externally. External handle with key and internal security release. With pedestrian non-slip floor. HACCP certification.



| | | | |
|----------------------|-----------|-------------------|--------|
| Door opening | 70x190 cm | Floor | Yes |
| Inside height cm | 203 cm | Panel thickness | 6 cm |
| Precise load - floor | 100 Kg | Temperature range | 0/+5°C |

Functional features

- Key-lock and internal security release.
- DOOR - Useful light cm 70x190h, opening from left to right, positioned on the longer side of the cold room.
- Semi-recessed door, overhang 4 cm; advantage of less space outside, less volume to cool at the same flow rate and better seal thanks to the more sealant joint and to the larger magnetic gasket..
- Anti-slippable pedestrian FLOOR, polyurethane insulation density 40 kg / m³. Plated galvanized sheet metal 7/10, static capacity load 1500 Kg / m², punctual precise capacity load 100Kg.

Constructional features

- Polyurethane insulation without CFC and HCFC thickness 60 mm, density 38/40 kg/m³; K = 0,336 W/m²K.
- Modular prefabricated panels made from food-approved, non-toxic plastic-coated plate.
- Fixing: with two-point fasteners with alignment system.
- Corner units: non-toxic plastic-coated plate cladding, polyurethane insulation, rounded on inside and outside.
- Patented panel fastening system that assures assembly speed and tightness guarantee.
- HACCP certification: the chamber is compliant with the HACCP International standards.

Technical Data

| | | | |
|------------|----------------|--------------|----------------|
| Net Weight | 320 kg | Gross Weight | 355 kg |
| Dimensions | 215x215x215 cm | Packing | 122x207x109 cm |

COLD ROOM THICKNESS PANEL 6 CM, INTERNAL HEIGHT 203 CM, 8,4 CBM WITH FLOOR

Cold rooms