

REFRIGERATED DISPLAY UNIT +2/+10°C

Vertical refrigerated display unit. Display compartment double-glazed with tempered glass, outside screen-printed, lower structure in special steel on wheels and adjustable feet. Color: grey. Lighting through LED lights. Nr. 4 shelves in tempered glass, support on racks in stainless steel AISI 304. Flap doors, Softmotion pneumatic opening system. Control panel in black glass with electronic PCB, capacitive keys, HACCP alarms. Ventilated refrigeration with evaporator positioned in the lower part of the structure, automatic air defrosting.



Capacity	l 536	Cooling Unit	integrated
Energy consumption/year, kW/h	3519	Energy Efficiency Class	C
Method for energy consumption	EN 23953	Product fitting up	Free-standing
Refrigeration	Ventilated	Shelves Quantity	4
Temperature range	+2/+10°C		

Functional features

- Operating temperature: +2°C ÷ +10°C.
- Relative humidity: 70%.
- Power unit with refrigerant fluid R290.
- Electronic control board with HACCP alarm signalling.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Snap removable front dashboard for compressor cleaning operations.

Constructional features

- Display cabinet made entirely of hardened double glazing, with grey silk-screened glass. Lower structure in grey special steel.
- Display compartment with 4 tempered glass shelves. Dimensions of each shelf: 107 x 41 cm. Max load per shelf 20 kg. Support on AISI 304 stainless steel racks.
- Doors with full length integrated handle, easy to grip. Easily removable magnetic gasket.
- Soft-Motion system for pneumatic flap opening of the doors.
- Ventilated refrigeration through finned evaporator with anti-corrosion treatment, positioned in the lower part of the structure.
- Lighting inside the display compartment by means of high-intensity, anti-glare LED bars.
- Wheels and feet integrated in the lower structure (4).
- Installation allowed to an altitude up to 800 metres above sea level.

Standard equipment

- 4 tempered glass shelves.

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	260 kg
Gross Weight	292 kg	Electric Power	0,92 kW
Dimensions	120x66x143 cm	Packing	130x76,5x166 cm