

## REFRIGERATED DISPLAY UNIT +2 ÷ +10°C COLOR WHITE

Vertical refrigerated display unit. Display compartment double-glazed with tempered glass, outside screen-printed. Color: white Lighting through high brightness LED bars. Nr. 5 tempered glass shelves, rear support racks in AISI 304 stainless steel. Ventilated refrigeration with evaporator positioned in the lower part of the structure, automatic air defrosting. Control panel with electronic PCB, capacitive keys, HACCP alarms. Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0).



Climate class	4 (+30°C, 55% R.H.)	Energy consumption/year, kWh/a	1840
Energy Efficiency Class	B	Method for energy consumption	EN 23953
Refrigeration power at -10°C W	632	Temperature ranges, °C	+2/+10
Volume, gross, lt	324		

### Functional features

- Operating temperature: +2°C ÷ +10°C.
- Relative humidity: 70%.
- Power unit with refrigerant fluid R290.
- The control panel, with electronic circuit board with capacitive keys and communication port, is concealed by the bottom structure, although the display is always in view for monitoring correct operation of the unit. It allows precise control of operating parameters as well as HACCP alarm alerts.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0).

### Constructional features

- Display cabinet made entirely of hardened double glazing, with white silk-screened glass. Lower structure in white color (RAL 9010).
- Display cabinet with 5 tempered glass shelves. Dimensions of each shelf: 49 x 47 cm. Max load per shelf 12 kg. Rear support on racks in AISI 304 stainless steel.
- Door with integrated full-height handle, easy to take, not reversible on site. Easily removable magnetic gasket.
- Ventilated refrigeration through finned evaporator with anti-corrosion treatment, positioned in the lower part of the structure.
- Dynamic lighting with anti-glare high-luminosity LED strips: the type of light can be varied depending on the product displayed (3000K – 4000K – 5000K – 6000K). The display unit is also fitted with PIR Sense proximity sensor, which changes the light intensity as customers approach.
- Wheels and feet integrated in the lower structure (4).
- Installation allowed to an altitude up to 800 metres above sea level.

### Standard equipment

- 5 tempered glass shelves.

### Optional

- Accessory for display of bottles (diameter: 75 mm) vertical, horizontal or a combination of the two. Maximum vertical bottle capacity 42 on three shelves.
- APOLINK accessory: connectivity to APO.LINK portal for remote control of appliance (Industry 4.0).

### Technical Data



Angelo Po Grandi Cucine S.p.A. con socio unico - 41012 Carpi (MO) Italy - Strada Statale Romana Sud, 90  
web: [www.angelopo.com](http://www.angelopo.com) - email: [angelopo@angelopo.it](mailto:angelopo@angelopo.it)

30/10/2022

# P6V



*Working voltage* 230V 1N~ / 50Hz

*Net Weight* 178 kg

*Gross Weight* 198 kg

*Electric Power* 0,4 kW

*Dimensions* 60x64,5x184 cm

*Packing* 74x76x202 cm

REFRIGERATED DISPLAY UNIT +2 ÷ +10°C COLOR WHITE  
Vitrine refrigerate New Style