

REFRIGERATED DISPLAY UNIT +2 ÷ +10°C COLOR GREY

Vertical refrigerated display cabinet. Display cabinet made in in hardened double glazing, silk-screened exterior, lower structure in special steel on wheels. Color: grey. Lighting through LED lights. Nr. 5 tempered glass shelves, rear support racks in AISI 304 stainless steel. Control panel with electronic PCB, capacitive keys, HACCP alarms. Ventilated refrigeration with evaporator positioned in the lower part of the structure, automatic air defrosting.



Climate class	4 (+30°C, 55% R.H.)	Energy consumption/year, kW/h	2290
Energy Efficiency Class	C	Method for energy consumption	EN 23953
Refrigeration power at -10°C W	851	Temperature ranges, °C	+2/+10
Volume, gross, lt	457		

Functional features

- Operating temperature: +2°C ÷ +10°C.
- Relative humidity: 70%.
- Power unit with refrigerant fluid R290.
- Electronic control board with HACCP alarm signalling.
- Automatic defrosting system by air.
- Automatic condensation evaporation.
- Snap removable front dashboard for compressor cleaning operations.

Constructional features

- Display cabinet made entirely of hardened double glazing, with grey silk-screened glass. Lower structure in grey special steel.
- Display cabinet with 5 tempered glass shelves. Dimensions of each shelf: 70 x 47 cm. Max load per shelf 12 kg. Rear support on racks in AISI 304 stainless steel.
- Door with integrated full-height handle, easy to take, not reversible on site. Easily removable magnetic gasket.
- Ventilated refrigeration through finned evaporator with anti-corrosion treatment, positioned in the lower part of the structure.
- Interior lighting in refrigerated display through LED bars, front on the back of the door.
- Wheels and feet integrated in the lower structure (4).
- Installation allowed to an altitude up to 800 metres above sea level.

Standard equipment

- 5 tempered glass shelves.

Optional

- Accessory for display of bottles (diameter: 75 mm) vertical, horizontal or a combination of the two. Maximum vertical bottle capacity 84 on three shelves.

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	211 kg
Gross Weight	236 kg	Electric Power	0,52 kW
Dimensions	80,5x64,5x184 cm	Packing	89x76x202 cm