

MULTIFUNCTION BLAST CHILLER/FREEZER 50/25 KG/CYCLE

Multifunction blast chiller and freezer made of AISI 304 stainless steel. Main functions: blast chilling, blast freezing, slow cooking, holding, proving and retarder-proving, defrosting, drying, pasteurization, conservation. Production per cycle: 50 kg from +90°C to +3°C at product core in 90 minutes; 25 kg from +90°C to -18°C at product core in 240 minutes. Inner compartment useful for 10 levels, GN 1/1 or EN 60x40 containers. Control panel with electronic board, 7" color touch display; multi-point probe for temperature detection at the core of the product. Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0). Insertion of GN 1/1 containers from the wide side (53 cm). Door opening from left to right.



<i>Category</i>	blast chiller freezer multifunctional	<i>Cooling power</i>	W 2526 - cecomaf conditions
<i>Defrosting type</i>	cycle reversal (hot gas)	<i>Energy consumption, kWh/kg</i>	0,09 (chilling) - 0,268 (freezing)
<i>GN 1/1-EN tray insertion side</i>	53 - 60 cm	<i>Max level/containers</i>	nr. 10 GN 1/1 - 60X40
<i>Method for energy consumption</i>	EN 22042	<i>Production per cycle</i>	50 kg (+90°C÷+3°C); 25 kg (+90°C÷-18°C)
<i>Supplied core probe</i>	IFR Multipoint		

Functional features

- Production per cycle: 50 kg from +90°C to +3°C at product core in 90 minutes; 25 kg from +90°C to -18°C at product core in 240 minutes.
- Achievable temperature in chamber: -40°C/+85°C.
- Control panel positioned on the appliance door; electronic board with 7" color touch display; USB communication port for software updates via pen-drive; available languages: IT - EN - ES - DE - FR - NL - DK - PT.
- Cold functions (timed and/or with core probe detection mode, in Soft - Hard - Hard Plus mode): blast chilling, blast freezing, conservation = automatic passage to the conservation phase after the blast chilling / freezing cycle, pre-cooling, cooling.
- Hot functions (timed and/or with core probe detection mode, in vacuum mode also): slow cooking, thawing, holding, pre-heating, drying, pasteurization, proving and retarder-proving.
- Automatic cycles: blast chilling, blast freezing, slow cooking, slow cooking in vacuum, proving.
- Special cycles: (I.F.R.) blast chilling, it automatically optimizes the blast chilling process for any type of food, regardless of size and quantity; it prevents surface freezing, thanks to the use of the core probe of the product with three sensors, anisakis, yogurt, chocolate, pasteurization, drying, pre-cooling, pre-heating.
- Favourite programs: 100 "Favourite" programs can be stored (30 blast chilling cycles; 30 blast freezing cycles; 20 slow cooking cycles; 10 retarder-proving cycles; 10 defrosting cycles).
- Climate Class 5 (room temperature +40°C, relative humidity 40%) on electrical safety according to EN60335-2-89. Climate class 4 (room temperature + 30°C, relative humidity 55%) on load performance. Performances are guaranteed up to room temperature +43°C.
- Noise level: 72 dba.
- Internal humidity regulation: from 0% to 100%; humidity detection probe.
- Container insertion direction: side 53 cm for GN 1/1; side 60 cm for EN 60x40.
- Connection to APO.LINK portal for remote control of appliance through accessory (Industry 4.0).

Constructional features

- One-piece construction with round inner corners; exterior and interior in AISI 304 stainless steel; Scotchbrite finish; frame and door profiles in high temperature resistant Noryl material.
- Insulation with polyurethane foam injection, thickness 75 mm, without the use of CFC; eco-friendly HFO foaming agent with low GWP (Global Warming Potential).
- Hinged fan cover panel for easy access to the evaporator and fan during cleaning.
- Forced ventilation not directly on foods. Defrosting by reverse cycle (hot gas). Refrigerant gas: R452A.
- Four-circuit evaporator; anti-corrosion treatment, cataphoresis, powder coating.
- Internal deep pressed bottom, hole for draining the cleaning water.
- Inner compartment with demountable rack in wire AISI 304 stainless steel; 10 levels, clearance 71.5 mm, useful for GN 1/1 or EN 60x40 cm containers.
- AISI 304 stainless steel door equipped with self-closing device for openings of less than 90°; door stop to keep the door open and prevent the formation of unpleasant odors; full height external handle; 10 chamber magnetic gasket, easily removable; electrical resistance on the door frame; hinges on the right; reversible on site: no.
- Condensation by air; engine installed on board. Access to the condenser for cleaning without the use of tools. Automatic evaporation of condensation by wire resistance.
- Four valves (thermostatic, compensation, liquid solenoid, dedicated to the defrost phase) to optimize and guarantee processes / cycles.
- RS485 communication port placed on the back of the appliance for connection to an Ethernet cable (cable not supplied).
- AISI 304 stainless steel feet, height adjustable 102 ± 164 mm. Appliance height 1782 mm with feet adjusted to 150 mm; max appliance height 1796 mm, min 1734 mm.

Safety equipment and approvals

- Magnetic safety micro-switch for stopping internal motor fan with door opening.
- Safety thermostat at 120°C for chamber temperature.
- Visual and audible HACCP alarms: shown on the display; countless alarms recorded for up to one year; storage of up to 40 events.
- Steam injection counter to warn need for maintenance need on the nebulizer.
- The appliance complies with the european regulation EU 2015/1095 - Specifications for eco-friendly design. Productivity per cycle: 50 kg from + 65°C to +10°C at the core of the product in 120 min; 25 kg from +65° to -18°C at the core of the product in 270 min. The quantities indicated have been tested according to the EN 22042 standard with the following parameters: ambient temperature of 30°C; cooling to +10°C; freezing -18°C; appliance at full load; trays h 40 mm; tested product: mashed potatoes evenly distributed up to 35 mm with initial temperature between 65° and 80°C, duration 120 / 270min.

Standard equipment

- Temperature probe at the core of the product: heated, Multipoint with 3 sensors with intelligent recognition; placed inside the door on a special support, in a space-saving position.
- Tray holder rack.
- Stainless steel tray for condensation water collection, located under the appliance.

Optionals and Accessories

- Accessories on request: kit for connection to the APO.LINK portal; temperature-humidity detector-recorder; probe holder for liquids; racks to make the chamber compatible only with EN 60X40CM containers; containers and grids; wheels.

Technical Data

<i>Working voltage</i>	400V 3N ~ 50 ÷ 60 Hz	<i>Net Weight</i>	200 kg
<i>Gross Weight</i>	225 kg	<i>Electric Power</i>	4,5 kW
<i>Dimensions</i>	80,2x85,1x178,2 cm	<i>Packing</i>	87,4x92,1x205,4 cm