

REFRIGERATED SALAD COUNTER 0/+8°C

Salad counter with structure made in AISI 304 stainless steel. AISI 304 stainless steel reclining lid. Top equipped with nylon shelf. Top and compartment suitable for GN 1/1 containers. Ventilated refrigeration, automatic defrosting system. Automatic condensation evaporation. Control panel: on/off switch, digital thermometer/thermostat. Equipped with: 2 guides and 3 GN 1/1 cross bars for each compartment/door, 2 GN 1/2 cross bars to support containers on the top. Height-adjustable plastic feet for floor levelling.



Capacity	I 220	Climate class	4 (+30°C, 55% R.H.)
Cooling unit	W 200	Refrigerant/GWP	R600a
Temperature range	0/+8°C		

Functional features

- Upper compartment, open, refrigerated, for displaying GN containers with non toxic nylon portioning / preparation shelf.
- Tilting lid made up of two sliding elements with opening stop at 80°.
- Internal compartment useful for GN 1/1 containers.
- Control board, equipped with digital thermometer-thermostat and on/off switch.
- Refrigeration by means of static evaporator, foamed, positioned inside the structure; ventilation for air distribution.
- Operating temperature: 0° C ÷ + 8°C.
- Automatic air defrosting (compressor stop).
- Automatic condensation evaporation.
- The appliance' s outstanding reliability is also assured by the IP24 protection of its functional elements.

Constructional features

- AISI 304 stainless steel structure.
- Insulation thickness: 50 mm.
- Removable motor unit to facilitate maintenance operations, the condenser is equipped with an easily removable filter to facilitate periodic cleaning.
- "U"-flow air circulation to assure peak cooling unit reliability.
- Refrigerant fluid R600a.
- Doors equipped with a self-closing device for openings inferior to 90°, integrated AISI 304 stainless steel handle with easy grip; Easy Clean magnetic gasket, easily removable.
- Refrigerated compartment with 2 doors.
- Refrigerated compartment with racks in AISI 304 stainless steel with a pair of guides each door, for supporting grids/ trays, easily removable.
- Drain hole to facilitate internal compartment cleaning operations.
- Plastic feet, adjustable in height.

Standard equipment

- The display compartment is supplied with: 3 x GN 1/1 bridge-bars, 3 x GN 1/2 bridge-bars and 3 x GN 1/6 bridge-bars for the support of containers.
- The under compartment is supplied with: pairs of guides.

Optionals and Accessories

- Guides to support trays-grids, GN containers of different sizes, grids and bridge-bars.

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	81,5 kg
Gross Weight	102 kg	Electric Power	0,143 kW

SA90



Dimensions

90x70x88,3 cm

Packing

96x76x102 cm

REFRIGERATED COUNTERS
REFRIGERATED SALAD COUNTER 0/+8°C