

REFRIGERATED TOP ON REFRIGERATED CUPBOARD - 3 GN

Printed top 3 cm deep, with rounded corners, capacity n.3 GN 1/1. Temperature range 0/ +8°C, 50 mm insulated. Digital temperatures control. Top in AISI 304 stainless steel, 1,5 mm thick. Lower cupboard: refrigerated version +4 +8 °C, digital temperature control. The block must necessarily be completed with paneling, choosing the type of panel preferred.



Capacity	3 GN	Refrigerant	R290
Refrigerant charge, kg	0,065		

Constructional features

- Top in AISI 304 stainless steel, 1,5 mm thick with sides preset to mechanical bayonet-type fitting. Top height 40 mm, front part in sight 85 mm.
- AISI 304 stainless steel pressed well with rounded corners, 30 mm deep.
- Cold compartment dimension 350x535x325H mm - N. 1 compartment GN 1/1.
- Independent digital temperature controls.

Technical Data

Working voltage	230V 1N~ / 50 ÷ 60Hz	Net Weight	119 kg
Gross Weight	131 kg	Electric Power	0,2 kW
Dimensions	120x83x90 cm	Packing	125x88x108 cm

REFRIGERATED TOP ON REFRIGERATED CUPBOARD - 3 GN
Self-Service and Drop-in