

REFRIGERATED WELL ON REFRIGERATED CUPBOARD - 4 GN

Pressed well 170 mm deep with rounded corners , endowed with bridge-bars to hold containers, capacity n.4 GN 1/1. Temperature range 0/ +8°C, 50 mm insulated. Digital temperatures control. Top in AISI 304 stainless steel, 1,5 mm thick. Lower cupboard: refrigerated version +4 +8 °C, digital temperature control. The block must necessarily be completed with paneling, choosing the type of panel preferred.



<i>Capacity</i>	4 GN	<i>Refrigerant</i>	R290
<i>Refrigerant charge, kg</i>	0,08		

Constructional features

- Top in AISI 304 stainless steel, 1,5 mm thick with sides preset to mechanical bayonet-type fitting. Top height 40 mm, front part in sight 85 mm.
- AISI 304 stainless steel pressed well with rounded corners, 170 mm deep.
- Cold compartment dimension 800x535x325H mm - N. 2 compartments GN 1/1.
- Independent digital temperature controls.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50 ÷ 60Hz	<i>Net Weight</i>	116 kg
<i>Gross Weight</i>	128 kg	<i>Electric Power</i>	0,2 kW
<i>Dimensions</i>	150x83x90 cm	<i>Packing</i>	155x88x108 cm

REFRIGERATED WELL ON REFRIGERATED CUPBOARD - 4 GN
Self-Service and Drop-in