

DISPLAY UNIT WITH 3 LEVELS, ROLLER SHUTTERS AND REFRIGERATED WELL ON OPEN CUPBOARD - 4 GN

Three levels showcase on pressed well 170 mm deep with rounded corners, endowed with bridge-bars to hold containers, capacity n.4 GN 1/1. Front closing through roller shutter, rear side through sliding doors. Showcase temperature range +6 +14°C, well 0 / +8°C, well insulation 50 mm. Digital temperatures control. Top in AISI 304 stainless steel, 1,5 mm thick. Lower cupboard: neutral open version. The block must necessarily be completed with paneling, choosing the type of panel preferred.



DISPLAY UNIT WITH 3 LEVELS, ROLLER SHUTTERS AND REFRIGERATED WELL ON OPEN CUPBOARD - 4 GN

Self-Service and Drop-in

Capacity	4 GN	Refrigerant	R455A
Refrigerant charge, kg	1,4	Showcase	Yes

Functional features

- The sliding door glasses on the operator side are fully supported from the top in order to provide a smooth, easy-to-clean surface.
- The showcase is lightened inside by LED-lights oriented towards the inside compartment, not disturbing customers and enhancing the visibility of the exposed products.

Constructional features

- Top in AISI 304 stainless steel, 1,5 mm thick with sides preset to mechanical bayonet-type fitting. Top height 40 mm, front part in sight 85 mm.
- Three levels showcase in tempered glass; they can be removed to ease cleaning operations.
- Digital temperature control

Technical Data

Working voltage	230V 1N~ / 50Hz	Net Weight	156 kg
Gross Weight	172 kg	Electric Power	1,55 kW
Dimensions	150x83x185 cm	Packing	155x88x203 cm