

REFRIGERATOR +2°C ÷ +10°C FOR TROLLEYS

Refrigerator with structure made in AISI 304 stainless steel panels. Storage chamber suitable to trolleys for 20 GN 2/1 - EN 60x80 cm containers. Ventilated cooling system, evaporator positioned outside the refrigerating chamber. Control panel with electronic circuit board, HACCP alarms signaling. Hot gas defrosting.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy Efficiency Class</i>	product are excluded from the European energy classification label according to EU Regulation 2015/1094
<i>LWA dB(A)</i>	62	<i>Net usable volume, lt</i>	1450
<i>Refrigerant charge, kg</i>	0,115	<i>Refrigerant/GWP</i>	R290/3
<i>Refrigeration power at -10°C W</i>	610	<i>Temperature range</i>	+2/+10°C
<i>Volume, gross, lt</i>	1526		

Functional features

- Operating temperature: +2°C ÷ +10°C.
- Reliability tested up to + 43°C.
- Power unit with refrigerant fluid R290.
- Control panel with electronic circuit board, HACCP alarm signaling: low and high temperature, black-out, core probe fails, high pressure and high condensation. Alarms are signalled by both visual and audio warnings; if chamber probe fails, the appliance continues operating on the basis of the mean compressor operating times prior to the malfunction. Operating temperature and relative humidity to 75% or 90% can be changed manually.
- Automatic defrosting by hot gas.
- Automatic condensation evaporation.
- Easy access to all controls and parts from the snap removable control board.
- Microswitch for internal fan stop and lamp switch on when door is open.

Constructional features

- Structure made of AISI 304 stainless steel panels, CFC-free expanded polyurethane insulation. Door, side panels and control panel with scotchbrite finishing.
- Insulation thickness: 70 mm.
- Ventilated refrigeration system through finned evaporator with anti-corrosion treatment, positioned inside the refrigerating chamber. means more storage space available.
- Chamber suitable to trolleys for GN 2/1 - EN 60x80 containers.
- Floor in AISI 304 stainless steel.
- Door on AISI 304 stainless steel hinges on the right, easily reversible on site, equipped with a self-closing device for openings inferior to 90°. Integrated full-height stainless steel handle with easy grip.
- Depth with door open: 1820 mm.
- Useful door clearance (WxDxH): 70 x 88 x 181.5 cm.
- Lighting through LED lamp with easy access.
- Key-operated lock.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	180 kg
------------------------	-----------------	-------------------	--------

Gross Weight	200 kg	Electric Power	0,32 kW
Dimensions	105,5x105,5x225,5 cm	Packing	116x119x240 cm

Refrigerators
REFRIGERATOR +2°C ÷ +10°C FOR TROLLEYS